



UT39+ series modern digital multimeters are portable devices designed for the electrical industry. They feature overvoltage and overcurrent alarm and high voltage protection, triggered during faulty operation. UT39C+ is suitable for HVACR maintenance with its temperature measurement feature. Designed according to CAT II 1000V/CAT III 600V safety standards.



● UT39C+

SPECIFICATIONS

	Range	UT39A+	UT39C+
DC voltage (V)	400mV/4V/40V/400V/1000V	±(0.5%+5)	±(0.5%+5)
AC voltage (V)	4V/40V/400V/750V	±(0.8%+3)	±(0.8%+3)
DC current (A)	40uA/400uA/4mA/40mA/400mA/10A	±(0.8%+3)	
	400uA/400mA/10A		±(0.8%+3)
AC current (A)	40mA/400mA/10A	±(1%+2)	
	4mA/400mA/10A		±(1%+2)
Resistance (Ω)	400Ω/4000Ω/40kΩ/400kΩ/4MΩ/200MΩ	±(0.8%+2)	
	400Ω/4000Ω/40kΩ/400kΩ/4MΩ/40MΩ		±(0.8%+2)
Capacitance (F)	4nF/40nf/400nF/4uF/40uF/400uF/4mF/10mF	±(4%+5)	±(4%+5)
Frequency (Hz)	10Hz~1MHz		±(1%+4)
Temperature	-40°C~1000°C		±(1%+4)
	-40°F~1832°F		±(1.5%+5)

Features


Display count		4000	4000
Transistor hFE		√	√
NCV			√
Diode		√	√
Frequency response	40Hz~400Hz	√	√
Range selection		Manual	Manual
Continuity test		√	√
Data hold		√	√
Backlight		√	√
Low battery indication		√	√
Auto power off		√	√

GENERAL CHARACTERISTICS

Power	1.5V battery (R03) × 2
Display	56.5mm x 36mm
Product color	Red and grey
Product net weight	330g
Product size	175mm x 83mm x 53mm
Standard accessories	Test leads, temperature probe (UT39C+)
Standard individual packing	Gift box, English manual
Standard quantity per carton	30pcs
Standard carton measurement	390mm x 355mm x 340mm
Standard carton gross weight	14.5kg



Super soft Insulator, meter is able to withstand 2m drop



Large screen



High quality dial



Collapsible support