



Specification	Range	UT60EU	UT60BT
<b>Certificates</b>	<b>CE, UKCA, cETLus</b>		
DC voltage (V)	1000V	±(0.5%+3)	
AC voltage (V)	1000V	±(0.8%+3)	
DC current (A)	10A	±(0.8%+3)	
AC current (A)	10A	±(1.0%+3)	
Resistance (Ω)	100MΩ	±(0.8%+2)	
Capacitor (F)	10mF	±(4.0%+5)	
Frequency (Hz)	99.99Hz~9.999MHz	±(0.1%+5)	
Duty cycle (%)	0.1~99.9%	±(3%+5)	
Temperature (°C/°F)	-40°C~1000°C/-40°F~1832°F	±4°C/±5°F	
<b>Features</b>			
Bluetooth	UT60BT only		
Display count	9999		
Auto range	√		
REL	√		
NCV	√		
Diode	√		
Continuity test	√		
Acousto-optic indication (NCV/continuity/battery power)	√		
Low battery indication	≤3.6V		
Data hold	√		
Auto power off	15Min		
Operating temperature	0°C~40°C		
Safety	CATII 1000V/CATIII 600V		

<b>Characteristics</b>	
Battery	1.5V AAA x 3
Product color	Red and gray
Product net weight	290g
Product size	169 x 81 x 46mm
Standard individual packing	Gift box, manual, thermocouple
Standard quantity per carton	20pcs
Standard carton size	420 x 320 x 300mm



UT60BT

UT60BT digital multimeter has a built-in Bluetooth module which can be used with iDMM2.0 app.



- Smart phone APP: iDMM2.0
- Works with UT-D07B Bluetooth adaptor
- Download from App Store or Google Play



UT60EU



UT60S

Specification	Range	Accuracy
<b>Certificates</b>	<b>CE, UKCA, cETLus</b>	
DC voltage (V)	9.999mV/99.99mV/999.9mV/9.999V/99.99V/999.9V	±(0.5%+3)
AC voltage (V)	9.999mV/99.99mV/999.9mV/9.999V/99.99V/999.9V	±(0.8%+3)
DC current (A)	999.9μA/999.9mA/9.999A	±(0.8%+3)
AC current (A)	999.9μA/999.9mA/9.999A	±(1.0%+3)
Resistance (Ω)	99.99Ω/999.9Ω/9.999kΩ/99.99kΩ/999.9kΩ/9.999MΩ/99.99MΩ	±(0.8%+2)
Capacitance (F)	9.999nF/99.99nF/999.9nF/9.999μF/99.99μF/999.9μF/9.999mF/99.9mF	±(4%+5)
Frequency	9.999Hz~9.999MHz	±(0.1%+5)
Duty cycle	0.1~99.9%	±(3%+5)
Temperature	-40°C~1000°C/-40°F~1832°F	±4°C/±5°F

Features	
Display count	9999
Auto range	√
NCV	√
Diode/REL	√
Continuity test	√
Acousto-optic indication(NCV/continuity/battery power)	√
Low battery indication	≤3.6V
Data hold	√
Auto power off	15Min
Operation temperature	0°C~40°C
Safety	CATII 1000V/CATIII 600V

General Characteristics	
Battery	1.5VAAA x3
Product color	Red and Gray
Product net weight	290g
Product size	169 x 81 x 46mm
Standard individual packing	Gift Box, Manual, Thermocouple
Standard quantity per carton	20pcs
Standard carton size	420 x 320 x 300mm