

These laser levelers are equipped with green LD laser, suitable for large or bright work places. Its applications include: horizontal, vertical, cross line projection for decoration, building construction, home decoration, renovation, furniture installation, flooring, and project layout.



LM312 wall mount
LM312 is suitable for
LM573LD-II/575LD/576LD only.



LM576LD

Specifications	LM570LD-II	LM573LD-II	LM575LD	LM576LD	LM585LD
Certificates (LM570LD-II/575LD only)	CE, UKCA				
Laser type	Green LD	Green LD	Green LD	Osram green LD	Osram green LD
Laser lines	2 lines	3D 12 lines	3D 12 lines	3D 16 lines	8 lines
Operating distance	10m	40m	40m	30m	30m
Laser accuracy	±3mm/10m	±3mm/10m	±3mm/10m	±3mm/10m	±3mm/10m
Outdoor pulse mode		√	√	√	√
Remote control		√	√	√	√
Self-leveling range	3°±1°	±3°	±3°	±3°	±3°
Self-leveling time	3s	<3s	<3s	<3s	<3s
Working hours	4h	>6h	>6h	>4h	>4h
Laser wavelength	520nm				
Laser class	2				

Features

Osram LD green laser(LM576/585LD)	Self-leveling mode & manual mode
Outdoor pulse mode	5200mAh Li-ion battery
Type-C DC-in port	includes wall mount (LM573LD-II/575LD/576LD)

Characteristics

Standard accessories	USB cable, adapter, English manual
Power	LM570LD-II: 1.5V battery x 2 (LR6); LM573LD-II/LM575LD/LM576LD/LM585LD: 3.7V Li-ion battery 5200mAh
Product size	LM570LD-II: 85.5 x 62 x 90.3mm; LM573LD-II: 119 x 89 x 138mm; LM575LD/LM576LD: 138 x 89 x 147mm; LM585LD: 138 x 89 x 136mm
Product net weight	LM570LD-II: 240g; LM573LD-II/LM575LD: 694g; LM576LD: 653g; LM585LD: 591g
Standard individual packing	Gift box, tool box
Standard quantity per carton	LM570LD-II: 20pcs; LM573LD-II/LM575LD/LM576LD/LM585LD: 4pcs
Standard carton measurement	LM570LD-II: 420mm x 320mm x 350mm; LM573LD-II/LM575LD/LM576LD/LM585LD: 620mm x 355mm x 325mm
Standard carton gross weight	LM570LD-II: 10.71kg; LM573LD-II/LM575LD/LM576LD: 10.63kg; LM585LD: 10.22kg